SELF-GOVERNING CAR FOR STOP SIGN AND BARRIER DETECTION

Dhananjay Narayan
Undergraduate,
Department of CSE, SRM IST

Alok Kumar
Undergraduate,
Department of CSE, SRM IST

Rajesh Borate
Undergraduate,
Department of CSE, SRM IST

A. Aruna
Assistant Professor,
Department Of CSE, SRM IST

Abstract— In the modern market, all vehicles are focused to be automated. A self-driving car is capable of sensing the surrounding environment and navigate itself without any interference from humans. As per the many public statistical data, the road accidents has increased and the amount of deaths involved in these accidents has also increased by a great margin. In this paper, we are proposing a system of Self-Driving car that can detect and sense the objects to avoid collision and inspects the traffic light by employing OpenCV Packages, Raspberry Pi and Machine Learning algorithms. This car will have the ability of self -governance. The need of human driving is completely eliminated. This gives relaxation to human drivers and also provides safe travelling experience.

Keywords: Computer Vision, Raspberry Pi, Self-Driving Car, Object Detection

1. INTRODUCTION

Computer vision is an emerging technology that has grown beyond the imagination of man and its applications are increasing day by day. It allows the computers to see, detect, recognize and process more than an human eye is capable of. It is being used in many applications these days. One Such Application is the Self Driving Car, otherwise known as an self-governing car. The self driving car has been in development since a long time. It started from low speed lane detecting vehicles through monochromatic images to completely automatic cars with improved features. [1][2] An self-governing car is an vehicle that is adept of comprehending its territory and navigating without human interference. They have the potential to use several technologies like Machine Learning, Augmented Reality, where a vehicle exhibits various statistics to the users. Self-Driving Cars have garnered attention from many research scholars and scientists alike. It has paved the way for future machines to completely take over the skill of human driving. It greatly serves its purpose in mitigating several crisis situations, traffic jams and security affairs that can arise on any normal road traffic. Most of the road mishaps occur due to driver errors such as lack of concentration, sleep deprivation etc. The Self driving cars will do the concentration part and unlike humans, these cars can drive themselves for as long as the power is provided to it. Thus it reduces the accident rates. The purpose of this paper is to employ some major features in a self-driving car. Features include:

1-Detection of traffic sign boards such as STOP Sign, LIMIT etc.
2- Detection of any barriers.
3-Traffic Light Recognition
4- Lane Detection

This paper includes implementation of the following systems:

1. Webcam and HC-SR04 Ultrasonic sensor as input
2. Raspberry Pi 3B+ as the processing unit.

In This paper the goal is to transform An RC Car To Handle three Major Tasks: Identifying Stop Sign , Traffic Light Detection, And Front Collision Avoidance.

2.PROBLEM STATEMENT

According To A Report In India, One Serious Road Accident Occurs Every Minute And 16 Die On Indian Roads Every Hour. 1214 Road Crashes Occur Every Day In India. Two Wheelers Account For 25% Of Total Road Crash Deaths. Today, 100% Of Drivers Licensed To Operate Cars Are Not Trained To Deal With Ethical Issues Or Tested On How The 'Right' Way To React In These What If Scenarios.

To Tackle This ,We Are Going To Build A Self Driving Car That Can Respond Smartly In These Situations And Doesn't Panic . It Will Obey The Traffic Rules Unlike Human And Can Minimize This Death Statistics

3.EXISTING SYSTEM

Various experiments and researches have been taking place since the 19th Century for automating the process of driving. The first such car was developed by Tsukuba Mechanical Engineering Laboratory in the year 1977. Now a days many of the major industrial companies has set their goals to develop an automated car with increased efficiency with more secure system. All the previous such attempts have employed algorithms that are not quite efficient and usually take more time to detect and analyze the objects. the use of machine learning in this field has been increasing now a days.

There is a demand for more efficient modules for the enhancement of security of these self -driving cars.

IV. Proposed System

We are proposing a remote-controlled car model that will be able to drive on its own by employing various machine learning algorithms. A camera will be mounted that will continuously capture images of the road through video streams and then by using HAAR Cascade Classifier, we will split the video streams into different frames and then further broken down into pixels for pre-processing and will extract features based on it. The different modules included are lane detection traffic signal detection, sign board recognition and obstacles detection. An ultrasonic also known as HC-SR04 is used for measuring the distance from all sides to avoid collision and the functioning of this will be monitored and controlled using Raspberry Pi.

V. ARCHITECTURE



Fig.1 Architecture

Advanced Image preparing calculation utilized here is protest identification utilizing Feature coordinating, which incorporates extraction of highlights from a picture and utilizing it to portray that picture. The picture handling steps are delineated in Fig.[4] In the Python code at first we discover the Keypoints and Descriptors of the format pictures and are put away as steady Numpy Arrays. These are kept for coordinating with the gushing video keypoints and descriptors. Video is gushed as one edge after other, this is done inside an unbounded circle. Each casing is taken and the keypoints and descriptors of them are acquired. Keypoints are regions of high pixel thickness and descriptors are 16*16 jumping zone around keypoints which help in recognizing one key point from another. Key points and Descriptors of a specific picture is extricated utilizing a SURF identifier Object (Speeded up Robust highlights).[3]

The following stage is including coordinating part where it looks at the highlights of format pictures with the highlights of relating outline that is being handled. It takes the descriptor of one component in first set and is coordinated with all different highlights in second set utilizing some separation count. Furthermore, the nearest one is returned. After Brute power coordinating of the highlights of format and casing picture 'k' best matches are acquired, where k is client characterized. The got matches are in type of (i,j) to such an extent that descriptor I in first set (format picture) has descriptor j in second set (outline that is being figured). Every one of the matches are acquired yet they can't just be utilized to call attention to the protest. These matches must be Filtered utilizing certain formulae to discover all the great matches.

The strategy utilized here is the David Lowes proportion test. It is more generally known as D Lowe's proportion test. So as indicated by D Lowe's technique the matcher question has a property called 'Separation' delineated as 'match distance', the lower the separation, the better the coordinated highlights. The 'k' closest neighbors or matches are taken and separation of every matcher question framed by every last one of k neighbors are found. On the off chance that k=2 then the proportion between the two matcher articles' separation trait is taken also, in the event that it is beneath a limit esteem (as a rule between 0.75 to 0.8) at that point, it is considered as a decent match. From the great matches, a few areas of a protest in a jumbled picture is known, this is sufficient to discover the protest from the jumbled picture (the present casing).

This procedure of finding the question is considered finding the homography. Homography is discovered utilizing the great matches got before. In any case, now the question we are hunting down in this jumbled picture may show up far, close or marginally tilted. [4] Thus, there is a need to change the viewpoint of survey the picture, keeping in mind the end goal to do this viewpoint change is connected alongside the Homography for all the more precisely depicting the area of the protest. At minimum four focuses must be come back to get the district of intrigue precisely. Another test experienced while finding the homography is the blunders that may happen while discovering great matches. Notwithstanding the D Lowes proportion, while finding homography a calculation called RANSAC (Random example accord) to sift through just the inliers from the homography we got before. This decreases blunders significantly further.



Fig. 2 Raspberry Pi 3B+,Pi camera and ultrasonic sensor mounted on Car

The strategy for RANSAC is to take an arrangement of highlights from the format picture and the course of action example of these highlights is noted. These are contrasted and the example of coordinating highlights got from the edge that is being figured. On the off chance that the design is a similar then these highlights are inliers, else they are exceptions. The separated blunder free co-ordinates are utilized to draw the jumping polygon around the Region of Interest. The Region of intrigue (ROI) limited by polygon is portrayed in the imminent segments. For straightforward question discovery in instances of identifying Stop signs, Speed constraining signs, person on foot crossing signs and so forth no further preparing is required. Be that as it may, for Traffic light acknowledgment, the got ROI is additionally scanned for Red shading by utilizing a calculation called Camshift.

This is a basic system and can be performed by setting edge esteems (HSV esteems) for red in inbuilt capacities for camshift. (H,S,V) values for unadulterated red is (0,255,255) where H-Hue(0 to 180) , S- Immersion (0 to 255), V-Value (0 to 255). The particular items are discovered utilizing these above calculations, yet the activities to be performed out when these objects are experienced must be done just at certain separate from the question. For this reason, a Distances total calculation must be produced.

VI. RESULTS

In this paper, an ongoing object recognition framework with a bound together neural system has been introduced. Dissimilar to other classifier-based methodologies, our model is prepared together, and assess each picture at just a single look at test time. Likewise, our methodology could reason all around about the setting of picture which diminishes the foundation mistake in object and obstacle detection. The framework for Traffic Sign and

Obstacle location in a Self-Driving auto was outlined and actualized utilizing Raspberry Pi and Atmega 328p microcontroller on a two wheel drive vehicle model.



Fig. 3 Self Governed Driving

The Feature identification and preparing in the framework was finished utilizing SURF finders and brute force matchers. The results may be as shown as in Fig 3. And Fig.4. [5] The field of self-driving vehicles is a territory where exceptional research is going on account of the requirement for a fault free driving knowledge. Numerous organizations like Mercedes and Tesla have implemented semi-self-driving autos and Google has developed a completely self-driving car. This is a territory where more examination is required as the activity conditions change step by step. The at present developed and accessible frameworks must be refreshed every now and again to guarantee the security of street activity.



Fig.4 Detection of Traffic Light

VI. Reference

[1]. Montemerlo and et al., Junior: The stanford entry in the urban challenge. Journal of Field Robotics: Special Issues on the 2007 DARPA Urban Challenge, 25(9): 569597, 2008.

[2]. Chris Urmson and et al., Autonomous Driving in urban environments: Boss and the urban challenge. Journal of Field Robotics: Special Issues on the 2007 DARPA Urban Challenge, 25(8): 425-466,2008.

[3] Mingfang DU, Junzheng WANG, Jing LI,Haiqing "Robot Robust Object Recognition based on Fast SURF Feature Matching" IEEE Chinese Automation Congress (CAC), 2013

[4] Renjith R, Reshma R and Arun KV, "Design and Implementation of Traffic Sign and Obstacle Detection in a Self-Driving Car using SURF Detector and Brute Force Matcher ", IEEE International Conference on Power, Control, Signals and Instrumentation Engineering (ICPCSI-2017)

[5] https://zhengludwig.wordpress.com/projects/self-driving-rc-car/